



# POWER BOOSTER

For Floor Sanders

- 1 Safe 4 wire locking inlet.
- 2 Safe 3 wire locking inlet.
- 3 Dedicated duplex circuit breaker 120V lines.
- 4 Rugged LED readout voltmeter for accurate output readings.
- 5 Low profile, 14 guage steel case.
- 6 Simple 3 position switch for high and low voltage operating conditions.

## PRODUCT DESCRIPTION

The Power Booster provides dedicated power outlets for any floor sanding jobsite and overcomes high and low voltage conditions with its “boost” and “buck” power selector switch. This tool is ideal for new construction projects where the power supply is limited and shared by various trades. Simply connect the power booster to the power source and control a personal isolated power source. The dedicated duplex circuit protected 120 V lines provide power for the operation of edgers, vacuums, compressors, saws and routers. The rugged digital LED readout voltmeter assures accurate output readings for peak performance of sanding machines and electrical operated tools.



## RECOMMENDED PRODUCTS



AVAC dust containment systems are the perfect mix of power and portability. At 26 and 12 gallon capacities, both models are easy to transport and are available with optional H.E.P.A. filters.



The FloorCrafter's superior cutting ability allows the contractor to sand the floor flat while also increasing jobsite productivity.

## TECHNICAL DATA

<b>Transformer</b>	8.4 KVA capacity
<b>Voltmeter</b>	Digital LED readout
<b>Inlet</b>	4 wire, locking, 250V/20A 3 wire, locking 250V/20A
<b>Outlet</b>	Duplex, circuit protected 3 wire straight blade, nylon face, 125V/20A
<b>Construction</b>	14 guage steel with non-marking gray rubber pads
<b>Dimensions</b>	9 x 9 x 6.75 in
<b>Weight</b>	25 lbs (11 kg)
<b>Warranty</b>	Parts & Labor - 2 yrs* *Excludes consumable wear items

Specifications are subject to change without notice.

## AVAILABLE MODELS

40590A - Power Booster

